

Accessories

Electrical heater for VAM


- » **Total fresh air solution (VAM + Electrical heater)**
- » **Increased comfort in low ambient temperature**
- » **No additional accessories required**
- » **Increased safety with 2 cut-outs**
- » **BMS integration**



www.daikin.eu



VH



Features

- > Total solution for fresh air with Daikin supply of both VAM and electrical heaters
- > Increased comfort in low outdoor temperature thanks to the heated outdoor air
- > Integrated electrical heater concept (no additional accessories required)
- > Standard dual flow and temperature sensor
- > Flexible setting with adjustable setpoint
- > Increased safety with 2 cut-outs: manual & automatic
- > BMS integration thanks to:
 - Volt free relay for error indication
 - 0-10VDC input for setpoint control

Specifications

	ELECTRICAL HEATER FOR VAM (VH)
Supply voltage	220/250V ac 50/60 Hz. +/-10%
Output current (maximum)	19A at 40°C (ambient)
Temperature sensor	5k ohms at 25°C (table 502 1T)
Temperature control range	0 to 40°C / (0-10V 0-100%)
Control fuse	20 x 5mm 250mA
LED indicators	Power ON - Yellow Heater ON - Red (solid or flashing, indicating pulsed control) Airflow fault - Red
Mounting holes	98mm X 181mm centres 5 mm ø holes
Maximum ambient adjacent to terminal box	35°C (during operation)
Auto high temp. cutout	100°C Pre-set
Man. reset high temp. cutout	125°C Pre-set
Run relay	1A 120V AC or 1A 24V DC
BMS setpoint input	0-10VDC

		VH1B	VH2B	VH3B	VH4B	VH4/AB	VH5B
Capacity	kW	1	1	1	1.5	2.5	2.5
Duct diameter	mm	100	150	200	250	250	300
Connectable VAM		VAM150FA	VAM250FA	VAM500FB	VAM800FB	VAM800FB	VAM1500FB
		-	VAM350FB	VAM650FB	VAM1000FB	VAM1000FB	VAM2000FB

For the selection of the appropriate capacity, please refer to the VAM selection software.



Daikin's unique position as a manufacturer of air conditioning equipment, compressors and refrigerants has led to its close involvement in environmental issues. For several years Daikin has had the intention to become a leader in the provision of products that have limited impact on the environment. This challenge demands the eco design and development of a wide range of products and an energy management system, resulting in energy conservation and a reduction of waste.

Products are not within the scope of the Eurovent certification programme.



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

Daikin products are distributed by: